

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Solventborne Aquapel water repellent exterior/interior

A-LL27904 5/12

WARNING

Read label before use. Keep out of reach of children. This material may be harmful if swallowed, inhaled or absorbed through the skin and causes skin irritation. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

AVOID BREATHING FUMES, VAPOURS, MIST OR SPRAY. USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING. Do not handle until all safety precautions have been read and understood. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Do not get in eyes, on skin or on clothing. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use explosion proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Store locked up. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint. Avoid release into the environment. Obtain special instructions before use. Clean up spillage.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT induce vomiting.

IF ON SKIN (or hair): Wash with plenty of soap and water; If skin irritation occurs: get medical advice. Take off contaminated clothing and wash before re-use.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

When seeking medical advice take this container with you. If exposed or concerned: Call a POISON CENTRE.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a water repellent on most porous building materials.

For full technical instructions see Data Sheet D655.

CONTAINS: White spirit >60% (Aust)

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority. Clean up spillage.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

FIRE: Use foam, carbon dioxide or dry chemical powder.



SHAKE WELL BEFORE USE



Resene Solventborne Aquapel is a clear silicone water repellent for application on most porous building materials to impart watershedding properties.

Preparation

- Ensure all surfaces to be treated are dry, free from dust, dirt and loose materials, oil and grease.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Flush clean with water.
- Remove oil and grease from surface using Resene Paint Prep and Housewash (see Data Sheet D812).

• All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

• This product may be used to treat a wide variety of surfaces. If the surface you propose to treat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller.

Application

- Resene Solventborne Aquapel can only be used over a porous surface that will allow the treatment to penetrate. It cannot be applied over a fully sealed surface then overcoated.
- Stir thoroughly before use. Apply by brush, roller or low pressure spray.
- Saturate the surface with Resene Solventborne Aquapel.
- Remove any Resene Solventborne Aquapel that gets onto glass to avoid the risk of staining.
- If it starts to rain, immediately cease application and cover all treated areas that have yet to dry out.
- Maintain good ventilation throughout the drying and curing period to ensure the treatment is properly cured. Poor ventilation may inhibit curing and performance.
- Maximum hydrophobicity (or water repellency) develops after a few days weathering.
- Recoat after 6 hours under normal conditions.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



UN NO. 1263 – PAINT RELATED PRODUCT

FLAMMABLE LIQUID AND VAPOUR

Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep closed when not in use.



Resene

the paint the professionals use



In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

net contents 4 litres

Quick check

Use on: Most porous building materials.

Gloss level: None – fully penetrating.

Typical coverage: Dependent on surface porosity – typically 2.5 square metres per litre for concrete block, 8-10 square metres per litre for concrete (tilt, precast, plaster).

Dry time (minimum): Penetrates – up to 48 hours for solvent to evaporate.

Primer required: No.

Usual number of coats: 1-2 to achieve saturation.

Application method: Low pressure spray is best, brush or roller.

Thinning and clean up: Mineral turps.

Colour range: Clear.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.