

net contents 1 litre
tinter included

LL1861901 12/13

WARNING

Read label before use. Keep out of reach of children. May be harmful if swallowed. Causes mild skin irritation. May cause an allergic skin reaction. May damage fertility or the unborn child. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

DO NOT BREATHE FUMES/MISTS/SPRAYS/VAPOURS. DO NOT EAT, DRINK OR SMOKE WHILE USING.
Do not handle until all safety precautions have been read and understood. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Store locked up. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/clothing. Do not allow contaminated clothing out of the workplace. Wash thoroughly after handling. Do not release to the environment. Clean up spillage. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposal of unwanted paint.

FIRST AID

IF SWALLOWED: Rinse mouth.
IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.
IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Rinse skin with water/shower with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

If medical advice is needed, have product container or label at hand. If exposed or concerned: Get medical advice/attention.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.
NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Liquid Hydrocarbons 500-550 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D38S.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing out brushes/rollers with the recommended thinner. Do not allow thinner to enter any drains. Refer to your local Council for disposal of dirty thinner.

IN CASE OF FIRE: Use foam, CO₂, dry chemical for extinction.



UN NO. 1263 – PAINT RELATED MATERIAL

FLAMMABLE LIQUID AND VAPOUR

Keep away from ignition sources such as heat/sparks/open flame/hot surfaces. No smoking.

WARNING

KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Resene

Sidewalk paving paint

exterior/interior



Resene Sidewalk is based on tough, flexible polyurethane resins to give maximum abrasion resistance in a one-pack finish. The surface finish of Resene Sidewalk is designed to reduce the hazard of slipping. Add Resene SRG Grit for extra slip resistance.

Preparation

- Ensure surfaces to be painted are in sound condition, dry, free from dirt, dust and loose material.
- New concrete must be allowed to cure for a minimum of 28 days.
- Concrete floors should be acid etched (see Data Sheet D83). If acid etching is impractical prime prepared surface with Resene Waterborne Smooth Surface Sealer (see Data Sheet D47a).
- Waterblasting is the best surface preparation if Resene Waterborne Smooth Surface Sealer is to be used.
- Oil and grease must be removed using Resene Paint Prep and Housewash (see Data Sheet D812). If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Efflorescence on masonry **must be treated**.
- Thoroughly scrape and sand to remove any weakly adhering or flaking paint and to provide a key for good adhesion.
- Fill cracks and holes in timber with an appropriate filler after priming.
- Round all sharp timber edges and sand back loose cellulose fibres. Any bare timber surface that has been left exposed to the weather for more than one week must be thoroughly sanded or treated with Resene TimberLock (see Data Sheet D48).
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**
- Test for moisture by taping a 30cm square of clear plastic to concrete floor. If moisture appears under plastic after 48 hours leave floor and repeat test until plastic is clear.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Priming

- Resene TimberLock is recommended on exterior timber and for restoration of badly weathered timber surfaces.
- Prime exterior timber with Resene Wood Primer (see Data Sheet D40).
- Resene Quick Dry (see Data Sheet D45) must be used as the first coat on Matai, Spotted Gum, Totara, fibre and particle board.
- On old or weathered cementitious substrates seal with one coat of Resene Sidewalk thinned 10% with turps and allow 24 hours before applying finish coats.

Topcoat

- Apply one coat and allow at least 16 hours to dry.
- For extra slip resistance add one pack (500gm) of Resene SRG Grit per litre to this first coat.
- Apply second coat and allow at least 24 hours dry time before subjecting painted areas to light foot traffic. Allow one week for full cure.
- If recoating after seven days thorough sanding of Resene Sidewalk is required.

- Maintain good ventilation throughout the drying and curing period to ensure the paint is properly cured. Poor ventilation may inhibit curing and performance.
- Trafficable areas coated with this unmodified product will not comply with the Building Act Clause D1.3.3(d). Product may be slippery when wet. For extra slip resistance add one pack (500 gm) of Resene SRG Grit per litre to the first coat.

Maintenance

(after a minimum of four weeks' drying)
See the Resene Caring for your paint finish brochure or the Resene website for full cleaning instructions.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.

Colours

Platypus 20SW20	Wine Trail 30SW20	Sentry 30SW30
Dark Ginger 20SW30	Slate 40SW10	Daytona 20SW10
Patio Red 10SW10	Botany Bay 30SW10	Grey Granite 40SW20
Teranova 10SW20	Tabac 20SW40	Amber Grey* 40SW30
Krakatoa 10SW30	Routeburn 20SW50	Pebble Grey 40SW40
Safari 10SW50	Moroccan Palm 30SW40	Marble* 40SW50
Pencarrow 10SW40	Tile Green 30SW50	

Colours are as close as printing process allows.

Quick check

Use on: Interior and exterior domestic surfaces and light industrial surface areas. Will chalk in exposed exterior situations.

Gloss level: Semi-gloss.

Coverage: 12.5 square metres per litre per coat (standard). 8.5 square metres per litre per coat (with added Resene SRG Grit).

Dry time (minimum): 4 hours. Drying is slowed by low temperatures and high humidity. Do not apply under damp conditions.

Recoat time (minimum): 16 hours. Maximum: Seven days.

Primer required: Yes dependent on surface.

Usual number of coats: Two.

Application method: Brush, roller or spray.

Do not spray with added Resene SRG Grit.

Thinning and clean up: Mineral turps.

Colour range: Resene Sidewalk colour palette.

Before use: Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 0800 737 363 (NZ) or visit the Resene website.



Solventborne Sidewalk SDS

Resene

the paint the professionals use



Solventborne Sidewalk TDS

In Australia: Resene Paints (Aust) Limited

7 Production Ave, PO Box 924, Beenleigh, Qld 4207

Phone 1800 738 383 Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited

Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045

Phone (04) 577 0500 Fax (04) 577 0600

Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as ISO9001 by Telarc SAL, an accredited certification body. This product complies with all the requirements of APAS Specification 0260/3 and 0280/3. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.