

Resene

Quick check

Terracotta Sealer

waterborne exterior/interior

SHAKE WELL BEFORE USE



LL2791050F
3/15

Resene Terracotta Sealer is a water repellent treatment formulated to help control efflorescence and give a long-term waterbeading effect to deter water penetration. Use on its own or as a primer under waterborne coatings. Will not prevent the penetration of driving rain or water under hydrostatic pressure.

Use on: Terracotta.

Gloss level: None, fully penetrating.

Coverage: Will vary according to substrate porosity, but typically less than 2 square metres per litre.

Dry time (minimum): Penetrates - up to 48 hours.

Recoat time (minimum): 6 hours.

Usual number of coats: One.

Application method: Low pressure spray is best, brush or roller.

Clean up: Water when wet; mineral turps when dry.

Colour range: Clear.

Product ingredients will settle on storage. Shake well to reincorporate before application.

WARNING Read label before use. Keep out of reach of children. Causes mild skin irritation. Causes eye irritation.

PRECAUTIONS USE WITH ADEQUATE VENTILATION. DO NOT EAT, DRINK OR SMOKE WHILE USING.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Wash all exposed external body areas thoroughly after handling. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods of cleaning equipment and disposing of unwanted paint. Do not contaminate any water supply. Avoid release to the environment.

FIRST AID IF SWALLOWED: Rinse mouth. Call a POISON CENTRE or doctor/physician if you feel unwell.

IF ON SKIN (or hair): Remove/take off all contaminated clothing and wash before re-use. Rinse skin with plenty of soap and water/shower. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical attention/advice.

Further information can be obtained from **AUST:** POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383. **NZ:** NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Octyltriethoxysilane 10-50 gms/L.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible on to newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

Preparation

- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80). Flush clean with water.
- Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).
- If the surface you propose to treat is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller.

Application

- Resene Terracotta Sealer can only be used over a porous surface that will allow the treatment to penetrate. It cannot be applied over a fully sealed surface then overcoated.
- Saturate the surface with Resene Terracotta Sealer.
- When coating pots, coat the inside of the pot and the outside of the pot.
- Remove any Resene Terracotta Sealer that gets onto glass to avoid the risk of staining.

- If it starts to rain, immediately cease application and cover all treated areas that have yet to dry out.
- Maintain good ventilation throughout the drying and curing period to ensure the treatment is properly cured. Poor ventilation may inhibit curing and performance.
- Maximum hydrophobicity (or water repellency) develops after a few days weathering.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383, Fax 1800 064 960

Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre,
Lower Hutt 5045, Phone (04) 577 0500, Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.