

net contents
1 litre

LL8100001 7/21

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.

PRECAUTIONS

AVOID BREATHING MISTS, VAPOURS OR SPRAYS. Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment. Obtain special instructions before use.

FIRST AID

IF SWALLOWED: Do NOT induce vomiting Immediately call a POISON CENTRE, doctor or first aider.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs get medical advice.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

IF BREATHING IS DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY.

When seeking medical advice take this container with you. If exposed or concerned: Call a Poison Centre.

Further information can be obtained from
AUST: POISONS INFORMATION CENTRE 131 126
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)
or call Resene 0800 737 363.

CONTAINS: Solvent Naphtha Petroleum, heavy aromatic 890 g/L.

For use as a paint thinner.

SPILLS

Eliminate all sources of ignition. Ventilate area, avoid breathing vapours.

Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove.

Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

FIRE

Blanket flames with dry chemical, carbon dioxide or foam. Wear self-contained breathing apparatus. Closed containers may explode when exposed to extreme heat.

The storage of flammable goods may require certification/licencing by the appropriate agency.

Consult the local Dangerous Goods Inspectorate.

Dispose of unwanted material in accordance with Local Body Regulations.

In every case it is recommended that the Safety Data Sheet is consulted prior to application.

Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

DANGER

KEEP OUT OF REACH OF CHILDREN

Resene Thinner No.10



Quick check

Thinner	Product
Mineral Turps	Mica Bond
No.2	Lusta-Glo; Super Gloss; Sureseal
No.3A	ArmourZinc 125
No.4	Vinyl Etch
No.5	Armourcote 608; Steel Fab
No.6	Armourcote 210 and 510; Alumastic; Imperite I.F. 503; Armourchlor Series (spray application); ArmourZinc 110
No.7A	Polymeric AV-8; Uracryl 400 Series (spray application)
No.8	Uracryl 400 Series (brush/roller application)
No.9	Zincilate 11
No.10	Slow Retarder; Rust-Arrest (brush/roller application)
No.11	Brush/roller application – Armourchlor Series; ArmourZinc 110; Steel Fab. Armourcote 515 (application above 35°C or over zinc rich primers); Medium Retarder
No.12	ArmourZinc 120; Armourcote 220, 512 and 515; Universal Cleaner; Rust-Arrest (spray application)
No.13	Imperite 413
No.17	Slow Retarder; Uracryl 802, Uracryl 803, Uracryl GraffitiShield

Refer to appropriate Product Data Sheet and Safety Data Sheet prior to application of, or clean up after use of, Resene Engineered Coating Systems products.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld, 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO 9001 by Telarc SAI, an accredited certification body. Printed on paper produced in manufacturing facilities which comply with environmental management systems EMAS and ISO 14001, using vegetable-based inks. Please recycle.



UN 3082, ENVIRONMENTALLY
HAZARDOUS SUBSTANCE.
LIQUID, N.O.S. (PAINTS)

COMBUSTIBLE LIQUID

Keep away from heat, hot
surfaces, sparks, open flames
and other ignition sources.
No smoking



Safety Data
Sheets