

Resene product labels are updated from time to time. This label is provided as a guide for this product and may differ from the label on the container you purchase.  
Please discuss your project with your local Resene ColorShop team or reseller to ensure you have the right products to give you the best quality finish for your specific project.

net contents  
1 litre

LL8110001 12-24

#### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes serious eye irritation. Causes mild skin irritation. May cause drowsiness or dizziness. May be harmful if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

#### PRECAUTIONS

AVOID BREATHING MIST, VAPOURS OR SPRAY. DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well-ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Store locked up. Wear protective gloves and clothing, eye and face protection. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and intrinsically safe equipment. Use non-sparking tools. Take action to prevent static discharges. Collect spillage. Avoid release to the environment.

#### FIRST AID

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTRE, doctor or first aider if you feel unwell. IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off immediately all contaminated clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms call a POISON CENTRE, doctor or first aider.

IF BREATHING IS DIFFICULT GET MEDICAL ATTENTION IMMEDIATELY. Call a POISON CENTRE or doctor or first aider if you feel unwell.

If medical attention is required: have product container or label at hand.

Further information can be obtained from AUST. POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: Naphtha petroleum, light aromatic solvent 690-880 g/L.

For use as a paint thinner.

#### SPILLS

Eliminate all sources of ignition. Ventilate area, avoid breathing vapours.

Use absorbent clean-up materials, such as fire retardant treated sawdust or diatomaceous earth to dike and contain spill. Scrape up and remove.

Collect and seal in properly labelled drums. Refer to local waste management authority. Keep out of public sewers and waterways.

#### FIRE

Blanket flames with dry chemical, carbon dioxide or foam. Wear self-contained breathing apparatus. Closed containers may explode when exposed to extreme heat.

The storage of flammable goods may require certification/licencing by the appropriate agency.

Consult the local Dangerous Goods Inspectorate.

Dispose of unwanted material in accordance with Local Body Regulations.

#### Be PaintWise

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information. Please recycle.

# WARNING

KEEP OUT OF REACH OF CHILDREN

# Resene Thinner No.11



#### Quick check

Thinner	Product
No.2	Lusta-Glo, Room Velvet, Super Gloss, Sureseal
No.3A	ArmourZinc 125
No.4	ArmourX Adhesion Etch Primer
No.5	Armourcote 608, Steel Fab
No.6	Alumastic, Armourchlor HB-F (spray application), Armourcote 510, ArmourX Cold Galv, ArmourX IF 503
No.7A	Uracryl 400 Series (spray application)
No.8	Uracryl 400 Series (brush/roller application)
No.9	Zincilate 11
No.10	ArmourX Rust-Arrest (brush/roller application), Slow Retarder
No.11	Armourchlor HB-F (brush/roller application), Armourcote 515 (application above 35°C or over zinc rich primers), ArmourX Cold Galv, Medium Retarder, Steel Fab
No.12	Armourcote 220 and 515, ArmourX Rust-Arrest (spray application), ArmourZinc 120, Universal Cleaner

Read the appropriate Safety Data Sheet before use.

For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

# Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Ltd  
7 Production Ave, PO Box 918, Ashmore City, QLD 4214  
Ph 1800 738 383 Visit [resene.com.au](http://resene.com.au)  
In New Zealand: Resene Paints Ltd  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph (04) 577 0500 Visit [resene.co.nz](http://resene.co.nz)



3



UN NO. 1263 – PAINT  
RELATED MATERIAL

**FLAMMABLE LIQUID  
AND VAPOUR**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.