

**WARNING**

**KEEP OUT OF REACH OF CHILDREN**

**Resene**

**Timber and Deck Wash**

exterior



**SAFETY PRECAUTIONS**

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. May be harmful if swallowed. Toxic to aquatic life.

**PRECAUTIONS**

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment.

**FIRST AID**

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

When seeking medical advice take this container with you. Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

For use as a timber wash.

CONTAINS: Sodium metasilicate, anhydrous 10-35gms/L.

**CAUTION**

- Do not add Resene Timber and Deck Wash to paint.
- Thoroughly clean spray equipment with freshwater immediately after use. Do not store concentrated or diluted product in metal or aluminium containers.

**Resene Timber and Deck Wash is a quick and easy way to clean surfaces, such as weatherboards and decks, prior to staining or painting.**

**Preparation**

• This product may be used to clean a wide variety of surfaces. If the surface you propose to clean is not referred to, try a small test area first or contact your local Resene ColorShop or reseller for advice.

**Application**

- Wear adequate protection. Use overalls, gloves, eye protection and suitable footwear.
- Mix with water and apply to saturate the surface. Keep the surface wet for 10-15 minutes. Do not use when the area to be cleaned is in direct sun.
- Scrub vigorously using a stiff nylon bristle broom or hard bristle scrubbing brush to loosen contaminants then wash off with copious quantities of freshwater.
- For best results, use high pressure washing (60-80 bar pressure). Do not use high pressure waterblasting as it will damage the timber surface. Always clean from the highest point down and if high pressure washing use a soft even fan-shaped water jet. Do not

use turbo heads. Scrubbing during low pressure washing (garden hose) will be required to remove surface contaminants.

- Ensure product is well rinsed off glass surfaces. Concentrated product left on glass surfaces may etch the surface.
- If heavy mould or moss deposits are present, treat the surface with Resene Moss & Mould Killer (see Data Sheet D80) prior to using Resene Timber and Deck Wash.

**Be PaintWise**

For tips on responsible disposal of paint, cleaning equipment and minimising the impact of your decorating on the environment see the Resene website. Do not discharge any paint into the environment. Resene PaintWise (NZ) or paintback.com.au (Australia) accepts residual unwanted paint and packaging. Or contact your Local Authority for disposal information.

Please ensure that use of this product is compatible with the substrate and surface preparation method. Resene does not accept any responsibility for the application of incorrect product to substrate. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

In Australia: Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Ph 1800 738 383 Visit [www.resene.com.au](http://www.resene.com.au)

**Resene**  
the paint the professionals use

In New Zealand: Resene Paints Ltd  
Vogel St, PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045  
Ph 04 577 0500 Visit [www.resene.co.nz](http://www.resene.co.nz)

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

**Quick check**

**Use on:** New or weathered timber.

**Appearance:** Pale orange.

**Mixing ratio:** One part Resene Timber and Deck Wash to three parts freshwater for weathered timber; or one part to six parts for new timber.

**Usage (diluted mix):** 10 square metres per litre per coat.

**Number of applications:** One.

**Application method:** Watering can or low pressure spray. Sufficient material must be applied to maintain wetness of the surface for 10-15 minutes.

**Thinning and clean up:** Water.



Timber and Deck Wash SDS



Timber and Deck Wash TDS



9 418022 031628

