

net contents 1 litre

LL2282101 12/17

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

PRECAUTIONS

AVOID BREATHING MIST, VAPOURS OR SPRAY.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

FIRST AID

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTRE or doctor, physician or first aider.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice or attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention.

If medical advice is required have product container or label at hand.

Further information can be obtained from

AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

CONTAINS: 3-Iodo-2-Propynyl Butyl Carbamate 1-5 gms/L, Benzotriazol derivatives 1-10 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D505.

SPILLS: Wear appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

CLEANING PAINT EQUIPMENT: Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Timber and Furniture Gel

enhance and protect

exterior/interior



KWILA

Resene Timber and Furniture Gel is a non-drip, easy to apply, waterborne gel-stain. It is formulated with CoolColour technology, and designed for use on a wide variety of new and weathered timber surfaces, including furniture, both inside and out.

Preparation

- Ensure surfaces to be painted are dry, free from dust, dirt and loose material, clean and free from loose wood fibres.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80) before coating.
- Treatment with Resene Timber and Deck Wash (see Data Sheet D813) is recommended for all substrates to remove dirt, natural stains and enhance the degree of product penetration.
- For repaints of existing penetrating stains remove any gross contamination and loose cellulose fibres.

All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.

- The finished colour is influenced by the colour and density of the timber. Try your chosen colour on a test piece of timber first.
- Consult your Resene ColorShop or Reseller for advice on coating severely weathered surfaces, exotic timbers, non-

standard timbers and exterior doors and windows.

- This product may be used to stain a wide variety of surfaces. If the surface you propose to stain is unsound or not referred to, try a small test area first or contact your local Resene ColorShop or Reseller for advice.

Precautions

- Contains powerful fungicides.
- Avoid skin contact.
- Gloves must be worn when application is by rubbing with fabric pad.
- Will not prevent checking of plywood.

Application

- Best results are obtained by rubbing the product with a lint-free cloth along the timber grain using medium pressure to help penetration.
- Application by brush is recommended for hard-to-reach places, such as between slats.
- On hardwoods a single coat is recommended; additional coats will form a low gloss film and may result in unsatisfactory weather aging. An additional coat is recommended for softwoods.
- This product is designed to penetrate the surface with assistance from rubbing and any excess must be wiped off. Failure to do so could result in reduced weather stability and cracks may appear in the resulting film.
- On softwoods, wet edge is reduced due to faster product penetration and extra care is required to avoid lapmarks.

- Strong colours may be hard to achieve on hardwood and heart timber due to lack of penetration.

- Overcoating with varnishes is not recommended.
- Not recommended on areas with a large surface area.
- Reapply Resene Timber and Furniture Gel each summer.

Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



Timber and Furniture Gel SDS

Resene

the paint the professionals use

In Australia: Resene Paints (Aust) Limited
7 Production Ave, PO Box 924, Beenleigh, Qld 4207
Phone 1800 738 383 Fax 1800 064 960
Email advice@resene.com.au or visit www.resene.com.au

In New Zealand: Resene Paints Limited
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045
Phone (04) 577 0500 Fax (04) 577 0600
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which complies with the requirements of environmental management systems EMAS and ISO14001, using vegetable-based inks.

Quick check

Use on: Timber surfaces.

Finish: Dependant on substrate and number of coats (low gloss film on new hardwoods).

Typical coverage: 10-14 square metres per litre depending on the timber.

Dry time (minimum): Generally less than 30 minutes. Drying is slowed by low temperatures and high humidity.

Recoat time (minimum): 1 hour.

Primer required: None.

Usual number of coats: Hardwood: one. Softwood: two.

Application method: Brush, lint-free cloth.

Clean up: Clean up with water when wet or mineral turps when dry but uncured.

Colour range: CoolColour Jarrah Tree, Kwila, Sheer Black and Silvered Grey. Application of a Resene CoolColour will reflect more heat than the same colour made using non-cool pigmentation and reduce heat related stress on the substrate; it will not make the stained surface cool to touch. If in doubt, use a lighter colour option to minimise heat build-up.

Before use: Stir well with a wide flat stirrer and also stir during application.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. Resene products are designed to be used as a system for optimal results. Substitution may cause substandard results or system failure. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.