

net contents 300ml

LL8172030 5/19

SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life.

PRECAUTIONS

DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, at an ambient temperature and avoid freezing conditions. Wear protective gloves and clothing, eye and face protection. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Call a POISON CENTRE, doctor or first aider if you feel unwell.

IF ON SKIN (or hair): Wash with plenty of soap and water. If skin irritation occurs get medical advice. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists get medical advice or attention. When seeking medical advice take this container with you.

Further information can be obtained from AUST: POISONS INFORMATION CENTRE 131 126 or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766) or call Resene 0800 737 363.

SPILLS Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to run off into waterways. Refer to local waste management authority.

WARNING

KEEP OUT OF REACH OF CHILDREN

Resene

Wintergrade Additive

to help waterborne Resene paint cure in the cold



Resene Wintergrade Additive is an additive for waterborne coatings providing extra protection against paint application in colder temperatures, so you can apply treated paint in temperatures down to 3°C.

Cold conditions can cause standard waterborne paint films to crack or powder and lead to premature paint failure. When using paint over winter, keep an eye on the temperature, both on the surface and in the air.

Remember a surface can be a lot colder than the air that surrounds it so you may find it's best to change your order of work and work on surfaces like plasterboard in the early morning and move to areas like concrete, which tend to be cooler in cold weather until they have had a chance to warm up a little.

Manufactured under a quality system certified as complying with ISO9001 by Telarc SAI, an accredited certification body. Printed on environmentally responsible paper, which meets with the requirements of environmental management system EMAS. Printed using de-inkable toners for recycling with no solvent emissions.

Instructions for use

- Always shake Resene Wintergrade Additive before use.
- Add 2% of Resene Wintergrade Additive to Resene waterborne paint:
 - + 10ml for a 500ml can
 - + 20ml for a 1L can
 - + 40ml for a 2L can
 - + 80ml for a 4L can
 - + 200ml for a 10L pail
- Do not add excessive amounts of Resene Wintergrade Additive - higher than recommended dosage does not provide additional benefit and may impact product performance.
- Do not use with any other Resene additive.
- Addition and mixing should be conducted outdoors or in well ventilated areas only.
- Thoroughly mix Resene Wintergrade Additive into paint and begin painting following the instructions for the Resene paint you are using.

USE THE TREATED PAINT WITHIN 10 WORKING DAYS. TREATED PAINT WILL THICKEN WHEN STORED FOR LONGER PERIODS AND WILL BECOME UNUSABLE.

Suitable for exterior or interior use. Only use in cool conditions less than 10°C. If the temperature is higher, use standard Resene paints without Resene Wintergrade Additive.



In every case it is recommended that the appropriate Safety Data Sheet is consulted prior to application.

Resene

the paint the professionals use

In Australia:

PO Box 924, Beenleigh, Qld 4207
Ph 1800 738 383 Visit www.resene.com.au

In New Zealand:

PO Box 38242, Wgtn Mail Centre, Lower Hutt 5045
Ph (04) 577 0500 Visit www.resene.co.nz