

# Wintergrade X-200

acrylic weathertight  
membrane

exterior

**WARNING**

KEEP OUT OF REACH OF CHILDREN



9 418022 030522

WHITE

LL7382210F 5/17

net contents  
10 litres  
tinter included

LL7382210B 5/17

### SAFETY PRECAUTIONS

Read label before use. Keep out of reach of children. Causes mild skin irritation. Harmful to aquatic life with long lasting effects.

### PRECAUTIONS

AVOID BREATHING DUST, FUMES, GAS, MISTS, VAPOURS, SPRAYS.

Store in original or correctly labelled container, tightly closed, in a well ventilated area indoors, away from foodstuffs, either between 15°C-20°C or at a cool, constant temperature. Avoid release to the environment. Dispose of empty container safely. Consult Resene checklist on environmentally acceptable methods for cleaning equipment and disposing of unwanted paint.

### FIRST AID

IF SWALLOWED: Immediately call a POISON CENTRE, doctor, physician or first aider.

IF ON SKIN (or hair): Rinse with plenty of soap and water. If skin irritation occurs get medical advice or attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing. If eye irritation persists: Get medical advice or attention.

When seeking medical attention take this container with you.

Further information can be obtained from  
AUST: POISONS INFORMATION CENTRE 131 126  
or call Resene 1800 738 383.

NZ: NATIONAL POISONS CENTRE 0800 POISON (764 766)  
or call Resene 0800 737 363.

CONTAINS: Mixed terpineols <10 gms/L.

For use as a decorative/protective coating.

For full technical instructions see Data Sheet D62a.

**SPILLS:** Use appropriate protective clothing. Absorb with sand or earth. Collect and seal in properly labelled drums. Do not allow to enter drains or to run off into waterways. Refer to local waste management authority.

**CLEANING PAINT EQUIPMENT:** Brush/roll out as much paint as possible onto newspaper before washing brushes and rollers. Dispose of wash-up water onto grassy/unsealed area or into inside sink/basin, NOT into outside stormwater drain where it may harm fish in local waterways.

**Resene Wintergrade X-200 is a low temperature curing acrylic weathertight membrane with excellent film build, adhesion, penetration, application and durability.**

### Preparation

- Ensure substrates to be coated are in sound condition, dry, free from dirt, dust, loose material, oil (including mineral oil based wood finishes or similar) and salt. Remove accumulated windblown salt by washing with Resene Paint Prep and Housewash (see Data Sheet D812).
- Waterblasting is the best surface preparation prior to painting of weathered cementitious surfaces.
- If mould is present, treat with Resene Moss & Mould Killer (see Data Sheet D80).
- Efflorescence on masonry **must be treated** (see Data Sheet D83).
- Wherever oil and grease are present ensure the surface to be painted is thoroughly cleaned using Resene Paint Prep and Housewash. Flush clean with water.
- For heavy contamination and cleaning of GRC panels scrub down with Resene Emulsifiable Solvent Cleaner (see Data Sheet D804) then rinse clean with water.
- All loose powdery material must be removed. If waterblasting is not possible thoroughly wire brush.
- Do not allow any rinsate to enter the stormwater system.
- **All sanding dusts may be harmful and appropriate protection must be worn. In particular dusts from old lead or chromate based paints or old building materials containing asbestos may be injurious to health if inhaled or ingested. Seek expert advice if the presence of these materials is suspected.**

- Fill cracks larger than 1mm with a suitable elastomeric paintable sealant after priming with Resene Sureseal (see Data Sheet D42) or Resene Quick Dry (see Data Sheet D45). Resene Wintergrade X-200 will bridge and fill smaller cracks.
- This product may be used to paint a wide variety of surfaces. If the surface you propose to paint is unsound or not referred to, try a small area first or contact your local Resene ColorShop or Reseller.

### Priming

- All surfaces which are in poor condition or affected by efflorescence or which are friable, powdery or chalky

must be primed with Resene Sureseal.

- Sealants - special coating requirements of construction sealants and fillers should be followed.
- Sound cementitious surfaces do not normally require a primer. Resene Concrete Primer (see Data Sheet D405) is recommended on properly prepared glossy cementitious surfaces.

### Application

- Apply one coat at five square metres per litre and allow three hours to dry.
- Apply second coat at 7.5 square metres per litre.
- Airless spray - use a Graco LTX 521 Tip or similar. Use a coarse filter in the system as the fibre reinforcement of Resene Wintergrade X-200 may clog finer filters.
- Standard spray - De Vilbiss JGA Gun with a D Tip DEX Needle and 107J Air Cap or equivalent.
- Concrete blocks and rougher surfaces require three coats to ensure weathertightness. Brush or roller are the preferred methods of application over blocks and essential at least for the first coat. The first coat must be applied at 5 square metres per litre and second and third coats at 7.5 square metres per litre.
- Back rolling will help to massage the product into pin holes and small cracks. Spray application in isolation is unlikely to fill these areas.

### Be PaintWise

For tips on minimising the impact of your decorating on the environment see the Resene website.



Wintergrade  
X-200 SDS

**Resene**

the paint the professionals use



Wintergrade  
X-200 TDS

**In Australia:** Resene Paints (Aust) Limited  
7 Production Ave, PO Box 924, Beenleigh, Qld 4207  
Phone 1800 738 383 Fax 1800 064 960  
Email advice@resene.com.au or visit www.resene.com.au

**In New Zealand:** Resene Paints Limited  
Vogel Street, PO Box 38242, Wellington Mail Centre, Lower Hutt 5045  
Phone (04) 577 0500 Fax (04) 577 0600  
Email advice@resene.co.nz or visit www.resene.co.nz

Manufactured under a quality system certified as complying with ISO 9001 by Telarc, an accredited certification body. Printed on environmentally responsible paper that complies with EMAS and ISO14001, using vegetable-based inks.

## Quick check

**Use on:** Exterior cementitious surfaces.

**Gloss level:** Very fine texture.

**Coverage:** First coat 5 square metres per litre per coat. Second coat 7.5 square metres per litre per coat.

**Dry time (minimum):** Dependent on weather conditions. Apply in temperatures 2°C-15°C. Application outside this temperature range may affect curing and application properties. Do not apply at temperatures below 2°C or when temperatures are liable to drop below this during the drying period.

**Recoat time (minimum):** 3 hours.

**Primer required:** Dependent on surface.

**Usual number of coats:** Two. Blockwork requires three.

**Application method:** Brush, synthetic fibre roller or spray.

**Clean up:** Water. Do not thin.

**Colour range:** White and colours off white.

**Before use:** Stir well with a wide flat stirrer.

Enjoy the Resene Promise of quality on premium paints. See your Resene ColorShop or the Resene website for a copy.

In every case it is recommended that the appropriate Data Sheet and Material Safety Data Sheet are consulted prior to application.

Please ensure that use of this product is compatible with the substrate and surface preparation method and that the colour in this container is the same as selected. When using multiple packs of this product on the same project please mix them together before use. Resene does not accept any responsibility for the application of incorrect product to substrate or the application of incorrect colours. For further painting advice and information, call 1800 738 383 (AUST), 0800 737 363 (NZ) or visit the Resene website.